LASYSTEMS - Brusselsesteenweg 208 - 1730 Asse - Belgium
Phone: +32-2-4531312 - Fax: +32-2-4531763
E-mail: info@lasystems.be

Aten CS1716I (DCP3006)

16-Port USB - PS/2 VGA KVM Over IP Switch with USB Peripheral port

PDF generated on: 22 June, 2015

Price details:

Price excl. VAT: 614.01 €
Eco fees: 0.00 €
VAT 21 %: 128.94 €

Product details:

Product code: DCP3006
EAN: 4710423776722
Manufacturer: Aten

742.95 €

* VAT included

Features
Management
- Convenient computer selection via front panel pushbuttons, hotkeys and multilingual on-screen display (OSD) menus
- Up to 32 concurrent logins
- Multilanguage web UI support featuring a tree-structured local and remote OSD
- Adjustable video quality for flexible adaptation to diverse network environments
- Auto Scan feature for monitoring user-selected computers
- Broadcast mode; operations simultaneously performed on all selected computers (software installation, system-wide shutdown, etc.).
- Firmware upgradable
- Backup and restore configuration and user account settings
- Event logging
- Enable/disable browser access
- IPv6 capable

Ease-to-Use Interface
- Browser-based and AP GUIs, together with a menu-driven OSD for the local console, provide a powerful, intuitive, user-friendly, multilanguage interface to minimize user training time and increase productivity
- Multiplatform client support (windows, Mac OS X, Linux, Sun)
- Multibrowser support (IE, Mozilla, Firefox, Safari, Opera, Netscape)
- Port names automatically reconfigured when station sequence is changed
- Panel array mode enables user to monitor multiple servers from single screen at the same time - each selected server's video output appears in a separate panel - users can easily select the number of panels to view
- Windows client and Java client software support; Java client works with all operating systems

Advanced Security
- Secure keyboard/mouse/video transmission via RC4 128 bit encryption
- 128 bit SSL browser access
- Two level password security - up to 64 user accounts with separate profiles for each
- External (Remote) authentication support: RADIUS, LDAP, LDAPS, MS Active Directory
- Support for IP/MAC Filter
- Local and remote access logged and authenticated

Virtual Remote Desktop
- Resizable remote desktop window
- Message board allows logged in users to communicate with each other, and allows a user to take exclusive control of the KVM functions
- Mouse DynaSync
- On-screen keyboard with multilanguage support
- BIOS-level access

Hardware
- 16-port remote access KVM switch - monitor and control up to 16 computers from a single KVM console
- Daisy chain up to 15 additional units - control up to 256 computers from a single console*
- Auto-sensing of station's position on daisy chained installations; no need for manual dip switch setting; front panel LED

indicates station's position
- Hot pluggable - add or remove computers without having to power down the switch
- Multiplatform support - Windows, Linux, Mac, and Sun
- Front panel USB hub allows connected computers to access USB peripherals
- Dual Interface - supports PS/2 or USB keyboard and mouse computer connections with automatic interface detection
- USB / PS/2 keyboard and mouse emulation - computers boot even when the console focus is elsewhere
- Supports USB keyboards for PC, Mac and Sun
- Superior video quality - up to 2048 x 1536; DDC2B for the local console; up to 1600 x 1200 @ 60Hz / 24 bit color depth for remote sessions
- Video DynaSync - stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution
- Rack mountable in a 19" (1U) system rack

Package Content
1x CS1716i KVM Switch
1x 2L-5202P PS/2 KVM Cable
1x 2L-5202U USB KVM Cable
1x LIN5-27X6-U21G Console Cable
1x Firmware Upgrade Cable
1x Mounting Kit
1x Foot Pad Set (4 pcs)
1x 0AD6-1605-24EG Power Adapter
1x Software CD
1x User Instructions

Main specifications:

Networking	
Ethernet LAN:	Y
Ports & interfaces	
Number of computers controlled:	16
DC-in jack:	Y
Ethernet LAN (RJ-45) ports:	1
Video	
Maximum resolution:	2048 x 1536 pixels
Design	
Colour of product:	Black
Rack mounting:	1U
LED indicators:	Y
Material:	Metal
Display	
Built-in display:	N
Performance	
Plug and Play:	Y
Scan interval:	255 s
Security algorithms:	802.1x RADIUS, SSL/TLS
Number of users:	32 user(s)
Power	
USB powered:	N
Power consumption (typical):	11 W
Operational conditions	
Operating temperature (T-T):	0 - 50 °C
Storage temperature (T-T):	-20 - 60 °C
Operating relative humidity (H-H):	0 - 80 %
Certificates	
RoHS compliance:	Y
Weight & dimensions	
Width:	160 mm
Depth:	433 mm
Height:	44 mm

Weight:	3000 g

Packaging content

Cables included:	KVM
Manual:	Y
AC adapter included:	Y

Other features

Connectivity technology:	Wired
Dimensions (WxDxH):	160 x 433 x 44 mm
Ports quantity:	16
Compatible operating systems:	Windows, Mac OS X, Linux, Sun
Power requirements:	5.3VDC
Colour depth:	24 bit
Browser supported:	IE, Mozilla, Firefox, Safari, Opera, Netscape
I/O ports:	1 x SPHD-18 M16 x SPHD-17 F1 x DB-25 M1 x DC In1 x RJ-45 F1 x RJ-111 x USB1.1 A

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herin, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.